



4 X 12



Herringbone



Basketweave

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Application
4 x 12	60	3.94" x 11.81"	124	384	3210	Bevel; No Chamfer	Standard, Shot Blast, Burnish, Burnish/SB	 Pedestrian
	80		93	288				  Pedestrian Auto

60 mm = 2.375 in (2 $\frac{3}{8}$ in); 80 mm = 3.125" (3 $\frac{1}{8}$ " ALL SPECIFICATIONS ARE APPROXIMATE.

ADDITIONAL INFORMATION:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C1782 Standard Specification for Utility Segmental Concrete Paving Slabs (latest edition).

More information on standards and installation procedures can be found by visiting the Concrete Masonry & Hardscapes Association (CMHA) at cmha.org.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.

The following CMHA Tech Specs provide installation guidance:

- PAV-TEC-024 - *Structural Design of Segmental Concrete Paving Slab and Plank Pavement Systems, provides information on commercial applications.*
- PAV-TEC-025 - *Construction Guidelines for Segmental Concrete Paving Slabs and Planks in Pedestrian Applications*

CMHA recommends using CMHA Certified Installers, who are trained in paver standards, materials, and techniques.

⚠ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.