


# CASCADA



**Herringbone**

| Description | Thickness (mm) | Approx Size (in) | Sq ft / Pallet | Stones / Pallet | Weight / Pallet (lbs) | Edge          | Finish                                    | Application                                                                                                                                                                                                                                                                                 |
|-------------|----------------|------------------|----------------|-----------------|-----------------------|---------------|-------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 5 x 10      | 80             | 4.92" x 9.84"    | 91             | 270             | 2835                  | Micro Chamfer | Standard, Shot Blast, Burnish, Burnish/SB |   <br>Pedestrian   Auto   Truck |

80 mm = 3.125 in (3 $\frac{1}{8}$  in); ALL SPECIFICATIONS ARE APPROXIMATE.

Permeable set applications require OBP Permeable Joint Chips. Sand-set applications require polymeric joint sand.

## ADDITIONAL INFORMATION:

Visit [ORCO.COM](http://ORCO.COM) for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition).

ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit the Concrete Masonry & Hardscapes Association (CMHA) at [cmha.org](http://cmha.org).

The following CMHA Tech Specs provide installation guidance:

- PAV-TEC-018-22 - *Construction of Permeable Interlocking Concrete Pavement Systems.*
- PAV-TEC-023-20 - *Maintenance Guide for Permeable Interlocking Concrete Pavements.*

CMHA recommends using CMHA Certified Installers who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at [ORCO.COM](http://ORCO.COM).

**⚠ WARNING:** This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).