




COUNTRY COBBLE



Combo Herringbone



Herringbone



I-Pattern

Description	Thickness (mm)	Approx Size (in)	Sq ft / Pallet	Stones / Pallet	Weight / Pallet (lbs)	Edge	Finish	Application
6 x 6 Square	60	5.51" x 5.51"	108	512	3021	Chamfer; No Chamfer	Standard Aged, Shot Blast, Burnish, Burnish/SB	 
6 x 8 Rectangle		5.51" x 8.27"	122	384	3379			
6 x 6 Square	80	5.51" x 5.51"	81	384	3021			  
6 x 8 Rectangle		5.51" x 8.27"	91	288	3379			

60 mm = 2.375 in (2³/₈ in); 80 mm = 3.125 in (3¹/₈ in); ALL SPECIFICATIONS ARE APPROXIMATE.

ADDITIONAL INFORMATION:

Visit ORCO.COM for the latest information on available color blends, solid colors, and patterns. Before ordering, always verify color and texture with pavingstone samples.

ORCO Block & Hardscape manufactures pavingstones in accordance with ASTM C936 Standard Specification for Solid Concrete Interlocking Paving Units (latest edition). And tested using ASTM C140 Standard Test Methods for Sampling and Testing Concrete Masonry Units and Related Units (latest edition).

ORCO certifies that our pavingstones average minimum compressive strength exceed 8000 psi with water absorption no greater than 5%.

For proper installation procedures, visit the Concrete Masonry & Hardscapes Association (CMHA) at cmha.org.

The following CMHA Tech Specs provide installation guidance:

- PAV-TEC-002-22 - *Construction of Interlocking Concrete Pavements*.

In addition, CMHA Guide Specifications provide information for installation of larger pavers, slabs, permeable systems, and using alternative setting beds like concrete, mortar, and bituminous asphalt. CMHA recommends using CMHA Certified Installers, who are trained in paver standards, materials, and techniques.

Complete ORCO Terms of Sale and applicable warranty information are available at ORCO.COM.

⚠ WARNING: This product when cut or ground can expose you to Silica crystalline (airborne particles of respirable size) which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.